



TouchPrint™ 5000 / 5500

High Quality Tenprint Images

Powerful Imaging Technology

- Scan resolutions available in 500 ppi or at more than 1000 ppi (exceeding the FBI certified requirement)
- Our patented Moisture Discriminating Optics™ ensures details in pores and no obscured ridge contours
- MegaView camera system provides 50% more pixels compared to conventional scanners
- Designed to eliminate variability that directly impacts image quality: no moving parts, no pads or coatings

Cabinet Configuration



The TouchPrint™ 5000 live scan appliance and TouchPrint™ 5500 cabinet booking station are capable of capturing detailed fingerprint images at either 500 or 1000 ppi. With advanced imaging power and anti-smearing and anti-smudging technologies, our fingerprinting solutions exceed FBI standard requirements.

SUPERIOR FINGERPRINT CAPTURE AND IMAGE QUALITY

Image quality is critical for live scan systems. Poor quality prints cannot be used to correctly identify or verify a subject on the first AFIS submission, resulting in higher rejection rates and lengthy processing times.

Our patented optics ignore moisture, dirt and latent prints left behind on the platen, making it easier to capture high quality images – consistently – regardless of the challenges faced, such as dry or sweaty fingers or an unclean platen. “Best in class” in image capture quality, rather than “good enough” is the choice to make in deciding which live scan to use in accurately identifying people.

The TouchPrint™ 5000 and TouchPrint™ 5500 are provided with the image clarity needed to prevent artifacts and capture important friction ridge detail. Both models boast high dynamic range sensor results in maximum contrast and gray scales, bringing out the minutiae and pore detail in the fingerprint image with virtually no distortion, which makes the image ideal for latent print comparison.

ADVANCED CABINET DESIGNS

This scanner is available in three models, a small desktop unit, a transportable unit (5000) and a full cabinet booking station (5500).

All models are designed with a platen encased in a durable, rugged housing environment. A sealed unit permits for deployment in demanding environmental conditions that may be dusty, wet, hot or humid.

The cabinet design has an ergonomic structure with a small foot print design, that allows for ease of use in space-constrained environments. The adjustable, 17” LCD flat panel monitor allows for optimal, high-resolution fingerprint imaging. In addition, optional accessory trays are available for extra workspace.

Desktop Configuration



Transportable Configuration



TouchPrint™ 5000 / 5500 Product Features Impacting Image Quality

FEATURES	BENEFIT
MegaView Camera System	Greater image detail – over 50% more pixels than conventional 1000 ppi scanners.
Grayscale	Linear, 256 levels with no lost detail from grayscale compression. Full ridge detail maintained for optimal latent comparisons.
Clean Image View™	100% better than the FBI specification for signal-to-noise ratio for greater ability to read features and ridge detail in fine ridge structures.
Balanced Image Distribution™	100-200% less geometric distortion equals enhanced accuracy of minutiae and ridge detail location.
AntiSmear™ Technology	Prevents smudging and smearing during finger rolls. High quality prints with less-skilled operators.
Clear Trace Imaging™	Prevents false minutiae by ignoring dirt or latents left on the platen. Provides greater uniformity across platen region. Less platen cleaning equals faster throughput.
Moisture Discriminating Optics™	Our patented optic technology ignores moisture and sweat to prevent loss of fine feature detail – essential for realizing the benefits of 1000 ppi scanning.
Auto Light Balancing	Maintains consistent image quality over time. Best prints all the time.

TouchPrint™ 5000 / 5500 Technical Specifications*

Model Number	TouchPrint™ 5000 and TouchPrint™ 5500
Scanning and Image Capture Resolution	Scan Resolution: 1000 ppi (v) x 1549 ppi (h) Scan Depth: 8 bits/pixel (256 gray levels) Capture Resolution: 1000 ppi (v) x 1000 ppi (h) Capture Depth: 8 bits/pixel
Active Image Dimensions	Multi-Finger Plain: 3.2 (h) x 2.0 (v) (nominal) inches Single Thumb Plain: 1.6 (h) x 1.5 (v) inches Rolled Impression: 1.6 (h) x 1.5 (v) inches
Image Quality	Geometric Distortion: Exceeds FBI IQS specification without calibration Linearity, Signal to Noise, CTF, Scanned gray levels: Meets or exceeds FBI IQS specifications
Illumination	White LED light panel for low operator eye fatigue and no color memory
Scanner Data Interface	IEEE 1394 Firewire
Size (appliance)	Deck Width: 12.5in (31.8cm); Deck Height: 6.3in (16.0cm); Deck Depth: 14.0in (35.6cm)
Size (cabinet)	Width: 24.0in (61.0cm); Height: 65.0in (165.1cm); Depth: 28.5in (72.4cm)
Weight (appliance)	14.0lb (6.4kg)
Power Requirements	110-120/220-240 VAC, 50/60Hz/-less 15.5 watts, Includes separate DC power module
Operating Environment (appliance)	Ambient temperature: 40°-104° F (5°-40° C) Relative humidity: 20-90% non-condensing Altitude: 0-7500 ft (2460 m) AMSL
Logical Scanner/Host Interface	<ul style="list-style-type: none"> • Software Development Kit (SDK) includes application program interface and device drivers for Windows XP and Vista operating system • (Available for licensed developers)

* Specifications subject to change without notice.
 © 2010 L-1 Identity Solutions Biometrics Division. All rights reserved. The trademarks identified herein are the trademarks or registered trademarks of L-1 Identity Solutions or other third party.

5705 W. Old Shakopee Rd.
 Suite 100
 Bloomington, MN 55437
 USA
 Telephone +1-952-932-0888
 Facsimile +1-952-932-7181

www.L1id.com